

The UltraRAE 3000+ is the most advanced Compound-Specific Monitor on the market. Its Photoionization Detector's (PID) extended range of 0.01 to 10,000 ppm in VOC mode and 10 ppb to 200 ppm in benzene-specific mode makes it an ideal instrument for applications from entry pre-screening during refinery and plant maintenance to hazardous material response, marine spill response and refinery down-stream monitoring.

## FEATURES

- Versatile VOC or Benzene-Specific modes
- Cost effective solution and low-cost RAE-Sep™ tubes
- Reflex PID Technology™
- Highly specific readings, combining a 9.8eV UV lamp and RAE-Sep™ benzene tube
- Built-in humidity sensor with Automatic temperature-controlled sampling time calculation
- See-through Sampling probe design for instant tube break-through visibility
- Highly connectivity capability through multiple wireless module options
- Multi-language support
- Easy access to lamp, sensor and battery in seconds without tools
- Dual detection mode for total benzene exposure assessment: 60-second snapshot or 15-minute STEL measurement
- High sensitivity to benzene provides a lower detection range for future benzene exposure limits
- Lower risk of false alarms through advanced speciation method
- Total VOC measurement mode with extended range of 0.01 to 10,000 ppm

## APPLICATIONS

- Confined space entry pre-screening during refinery and plant maintenance
- Hazardous material response
- Marine spill response
- Refinery down-stream monitoring



**CALL GEOTECH TODAY**  
**(800) 833-7958**

**Geotech Environmental Equipment, Inc.**  
2650 East 40th Avenue Denver, Colorado 80205  
(303) 320-4764 FAX (303) 322 7242  
email: sales@geotechenv.com website: www.geotechenv.com

Technical Specifications	
<b>Size</b>	10" L x 3.0" W x 2.5" H (25.5 x 7.6 x 6.4 cm)
<b>Weight</b>	26 oz. (738 g)
<b>Sensors</b>	Photoionization sensor with standard 9.8 eV or optional 10.6 eV or 11.7 eV lamps
<b>Battery</b>	- Rechargeable, external field-replaceable lithium-ion battery pack - Alkaline battery adapter
<b>Operating Time</b>	16 hours of operation
<b>Display Graphic</b>	4 lines, 28 x 43mm
<b>Display Readout</b>	- VOCs as ppm by volume - High and low values - STEL and TWA - Battery and shutdown voltage - Date, time, temperature
<b>Keypad</b>	1 operation and 2 programming keys, 1 flashlight on/off button
<b>EMC/RFI</b>	Compliant with EMC directive (2004/108/EC) EMI and ESD test: 100MHz to 1GHz 30V/m, no alarm Contact: ±4kV Air: ±8kV, no alarm
<b>IP Rating</b>	P-65, unit running
<b>Datalogging</b>	Standard 6 months at one-minute intervals
<b>Calibration</b>	2-point or 3-point calibration for zero and span. Reflex PID Technology™ Calibration memory for 8 calibration gases, alarm limits, span values and calibration dates
<b>Accuracy</b>	3% at calibration point
<b>Sampling Pump</b>	- Internal, integrated flow rate at 400 cc/min. - Sample from 100' (30 m) horizontally and vertically
<b>Low Flow Alarm</b>	Auto shut-off pump at low-flow condition
<b>Communication &amp; Data Download</b>	- Download data and upload instrument set-up from PC through charging cradle or using BLE module and dedicated APP - Wireless data transmission through built-in RF modem
<b>Wireless Network</b>	Mesh RAE Systems Dedicated Wireless Network
<b>Wireless Range (Typical)</b>	Up to 15 ft. (5 m) for BLE EchoView Host: LOS > 660 ft. (200 m) Safety Suite Premium & RAEMesh Reader: LOS > 660 ft. (200 m) Safety Suite Premium & RAELink3 Mesh: LOS > 330 ft. (100 m)
<b>Safety Certifications</b>	<b>US and Canada:</b> C CSA US, Classified as Intrinsically Safe for use in Class I, Division 1 Groups A, B, C, D <b>Europe:</b> ATEX II 2G EEx ia IIC T4 IECEx CSA 10.0005 Ex ia IIC/IIB GbT4
<b>Temperature</b>	-4° to 122°F (-20° to 50°C)
<b>Humidity</b>	0% to 95% relative humidity (non-condensing)
<b>Attachments</b>	Durable bright red rubber boot
<b>Warranty</b>	3 years for 10.6 eV lamp, 1 year for 9.8. eV lamp, pump, battery, sensor and instrument
<b>Wireless Frequency</b>	ISM license-free band. IEEE 802.15.4 Sub 1GHz
<b>Wireless Approvals</b>	FCC Part 15, CE R&TTE, Others1
<b>Radio Module</b>	Supports BLE, RM900 or Bluetooth

### Sensor Specifications

Gas Monitor	Range	Resolution	Response Time (T90)
<b>VOCs</b>	0 to 99.99 ppm	0.010 ppm	< 3 sec
	100 to 999.9 ppm	0.1 ppm	< 3 sec
	1000 to 9999 ppm	1 ppm	< 3 sec
<b>Benzene</b>	0 to 200 ppm	0.010 ppm	< 60 sec
<b>Butadiene</b>	0 to 200 ppm	0.010 ppm	< 60 sec

### Monitor Only Includes:

- UltraRAE 3000+ Monitor, Model PGM-7360
- Wireless communication module built-in
- Travel Charger
- RAE UV lamp and RAE-Sep™ Tubes
- Flex-I-Probe™ and short probe
- External filter
- Red rubber boot
- Alkaline battery adapter
- Lamp-cleaning kit
- Tool kit
- Lithium-ion (Li-ion) battery with universal AC/DC charger and international plug kit
- Operation CD-ROM
- Operation & Maintenance manual
- Soft leather carrying case

### Monitor with Accessories Kit:

- Hard transport case with pre-cut foam padding
- Charging/download cradle
- 5 porous metal filters and O-rings
- Organic vapor zeroing kit
- Gas outlet port adapter and tubing

### Optional Calibration Kit:

- Calibration gas, 34L, as specified
- Calibration regulator and flow controller

### Optional Guaranteed Cost of Ownership Program:

- 4-year repair and replacement guarantee
- Annual maintenance service

Specifications are subject to change.

CALL GEOTECH TODAY

(800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue Denver, Colorado 80205

(303) 320-4764 FAX (303) 322 7242

email: sales@geotechenv.com website: www.geotechenv.com