

Water Flow Probe

Digital Water Velocity Meter

The Global Water Flow Probe is a highly accurate water velocity instrument for measuring flows in open channels and partially filled pipes. The water velocity probe consists of a protected water turbo prop positive displacement sensor coupled to an expandable probe handle with a digital readout display. The water flow meter incorporates true velocity averaging for the most accurate flow measurements. Use for measuring flows in rivers and streams and monitoring velocity in ditches and canals.

FEATURES

- Easy flow monitoring
- Digital display in ft/sec or m/sec
- Lightweight, rugged, and reliable
- Used by water professionals worldwide for over 12 years
- Debris shedding turbo-prop
- Telescoping handle with staff gauge
- Displays instantaneous and true average velocity
- Rain-proof digital computer read-out
- Padded carrying case for easy storage
- Ideal for measuring flows in streams, rivers, canals, stormwater, wastewater, and industrial process waters



OPERATION

Turbo-Prop Sensor:

The Flow Probe incorporates the unique Turbo-Prop propeller sensor that uses the positive displacement technique for velocity sensing. The Turbo-Prop is designed to shed debris and is protected inside a 2" diameter housing. The probe housing may be placed directly on the bottom of pipes or streambeds for measuring low flows down to 2" in depth. The flow meter propeller rotates freely on its shaft with no mechanical interconnections for minimal friction. The Turbo-Prop, is easily removed for cleaning or replacement.

True Velocity Averaging:

A running average is started once both buttons are simultaneously pressed. This zeroes the display when the turbo-prop is placed into flowing water. As long as the propeller remains in the flow, the averaging continues. Once the average reading becomes steady, the true average velocity has been obtained. When you pull one of Global Water's environmental flow meters from the water, the average value is frozen on the display until reset.

Probe Handle:

The Flow Probe handle can telescope from 3 feet to 6 feet in length (FP101) or 5 feet to 15 feet (FP201). It is constructed of anodized aluminum for light weight and long life. The Flow Probe may be easily extended up to 25 feet in length using PVC pipe and an extension cable. This allows for sewer flow measurements from street level and measuring of stream flows from low bridges. A 3 ft. mylar coated staff gauge (graduated in hundredths of a foot and centimeters) is attached to the lower section of the water velocity probe for instant water depth measurements and accurate propeller positioning.

Geotech Environmental Equipment, Inc.
 2650 East 40th Avenue • Denver, Colorado 80205
 (303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com

Water Flow Probe

Digital Water Velocity Meter

SPECIFICATIONS

Range:	0.3-25 FPS (0.1-8 MPS)
Accuracy:	0.1 FPS
Averaging:	True digital running average. Readings taken once per second.
Display Type:	LCD
Sensor Type:	Protected Turbo-Prop propeller with electro-magnetic pickup.
Weight:	2 pounds
Size:	Length: FP101 3' to 6' FP201 5' to 15'
Materials:	PVC, anodized aluminum, stainless steel bearing.
Power:	Internal watch type battery/1 year life
Operating Temp:	0° to 120° F
Carrying Case:	The Flow Probe is shipped in a padded carrying case.



CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.
 2650 East 40th Avenue • Denver, Colorado 80205
 (303) 320-4764 • **(800) 833-7958** • FAX (303) 322-7242
 email: sales@geotechenv.com website: www.geotechenv.com