



Hydrocarbon Recovery Systems

Geotech Gas Guzzler System

The Geotech Gas Guzzler is an easy-to-install product recovery system designed for shallow recovery operation with up to 25 feet (7.6m) of suction lift. The pump is usually mounted at the well head or in a 12" (30.5cm) minimum sump and will deliver approximately 0-4 GPM (0-15 LPM) while using 2-6 CFM (.06-.17cm) of air, depending on the suction lift, pumping rate, and total discharge head.

FEATURES

- Non-metallic, corrosive resistant pump housing assembly
- Variable speed pump matches well recharge rate
- No controller required
- Choice of 2" or 4" (5cm or 10cm) Skimmer systems
- The 4" (10cm) floating Skimmer can accommodate groundwater fluctuations in excess of 24" (61cm) and skim free floating product down to a sheen
- 100 feet (30.5m) of tubing
- Tank overfill sensor
- Optional accessories:
 - Air compressor
 - Extended travel buoy on 4" Skimmers
 - 4" (10cm) heavy oil Skimmer
 - 4" (10cm) high temperature Skimmer
 - Protective stainless steel screen



CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com