

Soil Vapor Sampling Kits

AMS Gas Vapor Probe (GVP) Kits

Excellent for monitoring and sampling hydrocarbon spill sites, near underground storage tanks and pipelines.

AMS GVP kits use an AMS slide hammer or an electric rotary drive hammer drill and GVP drive extensions to insert a stainless steel GVP tip to the desired sampling depth.

FEATURES

- Can access the sampling point at depths of 9 ft. with the supplied extensions
- Sample soil vapor or shallow groundwater
- Select either Dedicated or Retract-a-Tip Gas Vapor Probe Tips
- Two types of kits are available:
 - Regular Gas Vapor Probe Kits
 - Heavy-Duty Gas Vapor Probe Kits
- Can be used for sub-slab vapor monitoring



KIT SPECIFICATIONS

Heavy -Duty GVP Kit with Dedicated Tips, Flighted Augers and Bosch 1124EVS Hammer Drill

AMS Part #209.93

Includes: Ten GVP dedicated tips with umbrella, Retract-A-Tip (included with Retract-A-Tip kit options only), 1½" wild bore bit, 5/8" tip drive end, four 3' GVP 5/8" extensions, 5/8" x 3' heavy-duty extendable tile probe base, three 5/8" x 3' heavy-duty tile probe extension, external drive adapter ¾" ID, SDS-Max drill adapter, SDS-Max 1½" carbide bit, slide hammer, slide hammer adapter ¾" OD, hand pump, 3/16" ID x ¼" OD x 250' fluoropolymer tubing, removal jack AMS deluxe carrying case, AMS GVP manual, GVP instruction DVD video, 2½" wild bore bit (SDS-Max) rather than a 1½", as well as, 2" carbide drill bit, 2" x 36" flighted lead auger with hard surfaced tip, two 2" x 36" flighted extensions, SDS-Max drill adapter.

177.00 lbs.

Heavy-Duty GVP Kit with Dedicated Tips

AMS Part #209.24

Includes: Ten GVP dedicated tips with umbrella, Retract-A-Tip (included with Retract-A-Tip kit options only), 1½" wild bore bit, 5/8" tip drive end, four 3' GVP 5/8" extensions, 5/8" x 3' heavy-duty extendable tile probe base, three 5/8" x 3' heavy-duty tile probe extension, external drive adapter ¾" ID, SDS-Max drill adapter, SDS-Max 1½" carbide bit, slide hammer, slide hammer adapter ¼" OD, hand pump, 3/16" ID x ¼" OD x 250' fluoropolymer tubing, removal jack AMS deluxe carrying case, AMS GVP manual, GVP instruction DVD video, 2½" wild bore bit (SDS-Max) rather than a 1½", as well as, 2" carbide drill bit, 2" x 36" flighted lead auger with hard surfaced tip, two 2" x 36" flighted extensions, SDS-Max drill adapter.

141.00 lbs.

GVP Kit with Dedicated Tip

AMS Part #209.19

Includes: Ten GVP dedicated tips with umbrella, Retract-A-Tip (included with Retract-A-Tip kit options only), 1½" wild bore bit, 5/8" tip drive end, four 3' GVP 5/8" extensions, 5/8" x 3' heavy-duty extendable tile probe base, three 5/8" x 3' heavy-duty tile probe extension, external drive adapter ¾" ID, SDS-Max drill adapter, SDS-Max 1½" carbide bit, slide hammer, slide hammer adapter ¾" OD, hand pump, 3/16" ID x ¼" OD x 250' fluoropolymer tubing, removal jack AMS deluxe carrying case, AMS GVP manual, GVP instruction DVD video.

115.00 lbs.

Other Things You'll Need



Dedicated Gas Vapor Probe Tip



Retract-A-Tip Gas Vapor Probe Tip

AMS Tech Tip:

Pre-drill your boreholes with the flighted augers prior to insertion of your GVP extensions and sampling tips to increase the lifespan of your stainless steel sampling points. Pre-drilling with flighted augers also allows access to sampling points in horizontal and vertical angles.

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • **(800) 833-7958** • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com