

Water Quality Meters

Oakton Waterproof Testr 35 Meters

Oakton Testr 35 meters are waterproof, pocket-sized meters used for easy dip-style measurements of water. Never watch a Testr sink to the bottom of your tank or pond! These waterproof Testrs float, so there's no need to worry. Valox® housing and stainless steel electrodes offer good chemical compatibility and durability. All Testrs have replaceable sensors. Reuse the meter body many times without losing waterproof and dustproof protection.

FEATURES

- Waterproof, dustproof housings float
- Push-button calibration, HOLD function, and error messages
- Displays measured value along with temperature, press a key to toggle
- Waterproof Dual Parameter PCTestr™ 35 and PTTestr™ 35:
Two important measurements in one instrument
Choose from two models – Conductivity and pH or TDS and pH
- Waterproof Multi Parameter PCSTestr™ 35:
Five measurements in one instrument!



ACCESSORIES

Replacement sensors
Replacement batteries, 1.5V pack of six
Beltloop carrying pouch

SPECIFICATIONS

	PCTestr 35	PTTestr 35	PCSTestr 35
Range:			
Conductivity	0 to 1999 µS/2.00 to 20.00 mS	–	0 to 199 µS/1 to 1999 µS/2.00 to 20.00 mS
TDS	–	0 to 999 ppm/1.0 to 10.00 ppt*	0 to 99.9 ppm/100 to 999 ppm/1.0 to 10.00 ppt*
pH	0.0 to 14.0	0.0 to 14.0	0.0 to 14.0
Temperature	-0.0 to 50.0°C	-0.0 to 50.0°C	-0.0° to 50.0°C
Salinity	–	–	0 to 99.9 ppm/100 to 999 ppm/1.0 to 10.00 ppt* 0.0 to 1.00%
Resolution:			
Conductivity	1 µS/0.01 mS	–	0.1 µS/1 µS/0.01 mS
TDS	–	1 ppm/0.01 ppt	0.1 ppm/1 ppm/ 0.01 ppt
pH	0.1 pH	0.1 pH	0.1 pH
Temperature	0.1°C	0.1°C	0.1°C
Salinity	–	–	0.1 ppm/1 ppm/0.01 ppt/0.01%
Accuracy:			
Conductivity	±1% full scale	±1% full scale	±1% full scale
TDS	–	–	±1% full scale
pH	±0.1 pH	±0.1 pH	±0.1 pH
Salinity	–	–	±1% full scale
Temperature	±0.5°C, ±0.9°F	±0.5°C, ±0.9°F	±0.5°C, ±0.9°F
Calibration:	One-point push-button calibration	One-point push-button calibration	One-point push-button calibration
Power:	Four 1.5V alkaline batteries	Four 1.5V alkaline batteries	Four 1.5V alkaline batteries
Display:	4-digit LCD, dual line	4-digit LCD, dual line	4-digit LCD, dual line
Dimensions:	6½" L x 1½" W x 1½" H	6½" L x 1½" W x 1½" H	6½" L x 1½" W x 1½" H

*Maximum TDS range based on TDS factor of 0.5

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.
2650 East 40th Avenue • Denver, Colorado 80205
(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242
email: sales@geotechenv.com website: www.geotechenv.com