

Water Quality Meters



YSI EcoSense EC300A Conductivity/Temperature Meter

The YSI EC300A is designed for quick, accurate results in an economical platform. The ability to measure conductivity, salinity, TDS and temperature in a simple compact instrument allows the instrument to be used across multiple application sampling strategies.

FEATURES

- IP67 Waterproof housing
- · Rugged, weighted probe assembly
- Automatic temperature compensation
- · 4- and 10-meter field cables available
- · Conductivity, Salinity, TDS, Temperature
- Super-stable, four-electrode conductivity cell designed for the field
- · Calibration back-up
- Audio feedback
- · 1-Year instrument, electrode and cable warranty
- · Auto shutoff function after 30 minutes of inactivity
- 50 data set memory
- · CE compliant
- · Calibration solutions available

SPECIFICATIONS

| Temperature: Range Resolution Accuracy | -10° to +90°C (14° to 194°F) 0.1°C ± 0.2 °C or ± 0.4 %, whichever is greater |
|--|--|
| Conductivity: Range 0 to 499.9 μS/cm 0 to 4999 μS/cm 0 to 49.99 mS/cm 0 to 200.0 μS/cm | $0.0 \mu S$ to 200 mS, with auto ranging Resolution Accuracy (meter & probe) $0.1 \mu S$ /cm $\pm (1\% of reading + 2 \mu S$ /cm) $1 \mu S$ /cm $\pm (1\% of reading + 5 \mu S$ /cm) $0.01 m S$ /cm $\pm (1\% of reading + 0.05 \mu S$ /cm) $0.1 m S$ /cm $\pm (1\% of reading + 0.5 m S$ /cm) |
| Salinity: Range Resolution Accuracy | Calculated; 0.0 to 70.0 ppt 0.1 ppt ±0.2% FS |
| Total Dissolved Solids: | TDS in g/L calculated; enter constant values from 0.30 to 1.00, default value 0.65 |
| General: Reference Temp Temp Coefficient Default Cell Constant | 15.0° to 25.0°C (59° to 77°F) 0.0% to 4.0% 5.00 |

4.50 to 5.50

Thermistor, 10KΩ at 25°C



| Operating Range: Temperature Relative Humidity | 0° to 50°C (32° to 122°F) up to 95% |
|--|---|
| Size: | 3.1" W x 7.25" L x 1.45" D (78mm x 184mm x 37mm) |
| Weight w/Battery: | 0.6 lb. (272 gm) |
| Battery: Battery Life | One 9 volt included with purchase 500 hours |
| Calibration Back-up: | Yes |
| Audio Feedback: | Yes, all keys |
| Autolock Feature: | Yes |
| Memory: | 50 data set reviewable memory |
| Auto Shutoff: | Automatically powers off after 30 minutes of inactivity |
| Water Rating: | IP67 Waterproof |

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205 (303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242 email: sales@geotechenv.com website: www.geotechenv.com

Cell Constant Range

ATC Probe