

Water Quality Meters

Thermo Electron Russell RL060C Portable Conductivity/Temperature Meter

The Russell RL060C Conductivity meter from Thermo Electron is a rugged and affordable meter, ideal for measurements in the plant or field.

FEATURES

- 1 to 5 point calibration (1 per range)
- Simple operation, yet accurate results
- Auto-ranging capability detects appropriate measurement range and provides the user with \pm full scale accuracy with fast repeatable results
- Splash-proof keypad and optional boot makes bench-top operation easy
- Large liquid crystal display (LCD) provides easy viewing of units-of-measure and error codes
- Simple four-button operation makes the Russell RL060C the meter of choice for many applications
- Packages include meter and probe



SPECIFICATIONS

		Specification	Benefit
Conductivity	Range	0 to 199.9 μ S/cm 0 to 1999 μ S/cm 0 to 19.99 mS/cm	
	Resolution	0.1 μ S/cm 1 μ S/cm 0.01 mS/cm	
	Accuracy	\pm 1% full scale	
	Calibration Points	1 to 5 (1 per range)	Improved accuracy
Temperature	Range	0.0 to 100° C	
	Temperature Compensation	Auto/Manual	
	Resolution	0.1° C	
	Accuracy	\pm 0.5° C	
	Temperature Coefficient	2%/°C	
Auto-ranging Capability		Yes	
Hold Function		Yes	
Display		Custom LCD	Easy to read
Auto Off		after 17 minutes	Saves battery life
Power Requirements		4 AAA batteries	Worldwide operation
Battery Life		> 100 hours	

NOTE: System accuracy depends on all choice and measurement conditions. Above data generated under optimal/controlled circumstances.

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.
2650 East 40th Avenue • Denver, Colorado 80205
(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242
email: sales@geotechenv.com website: www.geotechenv.com