

Electric Powered Air Compressors



Electric Powered Air Compressor

This 4.5 gallon (19.8 L) roll cage air compressor is an oil free, direct drive operation. Air compressor is low maintenance with no oil to add or change and no belts or pulleys to replace. Great for outdoor use in all seasons with an easy cold weather start. Recommended for use with Geotech low-flow bladder sampling pumps or fractional CFM applications.

FEATURES

Long lasting, powerful induction motor

Fully enclosed panel protects the pump and motor

Centralized handle with cushioned grip

 Control panel with guick set regulator, tool, and tank pressure gauges, and two brass (no spark/ rust) push-to-connect couplers for added convenience

SPECIFICATIONS

Air Delivery 5 CFM @ 90 PSI

> (.14 CMM @ 6.2 BAR) 6.9 CFM @ 40 PSI (.2 CMM @ 2.76 BAR)

1.6 HP Motor

Low Amp Draw 15 A

> **CSA Listed** Yes

Handle Yes

Maximum Pressure 150 PSI (10.3 BAR)

Product Depth 22 in. (55.88 cm)

Product Height 18.5 in. (46.99 cm)

Product Width 22 in. (55.88 cm)

Product Weight 85 lbs. (38.55 kg)

Pump Housing Material Aluminum

Pump Type Oil-free direct drive 4.5 gal. (US) (17 L)

Tank Material Aluminum

Tank Pressure Gauge Yes

Tank Capacity

Twin Stack Tank Configuration

4-UL Certified **UL Listed**

Voltage 120 V



CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc. 2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242 email: sales@geotechenv.com website: www.geotechenv.com