

Geotech PRC Passive Skimmer

The Geotech Product Recovery Canister (PRC) is a passive skimmer designed to recover product-only (LNAPL) layers down to a sheen. The PRC features a floating intake that adjusts for groundwater fluctuations, a product canister for measuring recovered volumes, and a product drain valve designed to eliminate fluid splattering.

FEATURES

- Floating oleophilic intake auto adjusts for water level changes
- Ideal for extreme environments and low recovery applications
- Configured for dedicated or portable installations
- Choice of floating intake mesh sizes

2" PRC System:

- 12" (30.5 cm) effective buoy travel
- Oleophilic intake – 60 or 100 mesh
- Transparent collection canister
- Product drain valve
- 25' of suspension cable with adjustable clamp
- Optional protective SS screen

4" PRC System:

- 16" (40.6 cm) effective buoy travel
- Oleophilic intake (60 or 100 mesh)
- White collection canister
- Product drain valve
- 25' of suspension cable with adjustable clamp
- Slotted protective PVC screen



CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • FAX (303) 322-7242

email: sales@geotechenv.com • website: www.geotechenv.com

Geotech PRC Passive Skimmer

SPECIFICATIONS

4" PRC

	1 Liter	3 Liter	4 Liter
Dimensions	37.0" L x 3.5" OD (94cm x 9cm)	53.0" L x 3.5" OD (135cm x 9cm)	60.0" L x 3.5" OD (152cm x 9cm)
Empty Weight	8 lbs. (3.7kg)	15 lbs. (6.8kg)	16 lbs. (8.2kg)
Full Weight	9.5 lbs. (4.3kg)	19 lbs. (8.6kg)	25.5 lbs. (11.6kg)
Capacity	.26 gal.	.8 gal.	1.06 gal.
Min. Water Depth Required	18.5" (47cm)	35.0" (89cm)	43.0" (109cm)
Materials (All)	Stainless steel, brass, and engineered plastics		

2" PRC

	0.125 Liter	0.25 Liter	0.5 Liter	1 Liter
Dimensions	43.5" L x 1.75" OD (110cm x 4.4cm)	49.0" L x 1.75" OD (149cm x 4.4cm)	59.5" L x 1.75" OD (151cm x 4.4cm)	82.5" L x 1.75" OD (210cm x 4.4cm)
With Optional SS Screen	43.5" L x 1.88" OD (110cm x 4.8cm)	49.0" L x 1.88" OD (149cm x 4.8cm)	59.5" L x 1.88" OD (151cm x 4.8cm)	82.5" L x 1.88" OD (210cm x 4.8cm)
Empty Weight	2.9 lbs. (1.3kg)	3.1 lbs. (1.4kg)	3.5 lbs. (1.6kg)	5.2 lbs. (2.4kg)
With Optional SS Screen	4.3 lbs. (2.0kg)	4.5 lbs. (2.0kg)	4.9 lbs. (2.2kg)	6.6 lbs. (3.0kg)
Full Weight	3.1 lbs. (1.4kg)	3.5 lbs. (1.6kg)	4.3 lbs. (2.0kg)	6.7 lbs. (3.0kg)
With Optional SS Screen	4.5 lbs. (2.1kg)	4.9 lbs. (2.2kg)	5.7 lbs. (2.6kg)	8.1 lbs. (3.7kg)
Capacity	0.035 gal.	0.07 gal.	0.13 gal.	0.26 gal.
Min. Water Depth Required	23.5" (60cm)	29.0" (74cm)	39.5" (100cm)	62.0" (157cm)
Materials (All)	Stainless steel, brass, and engineered plastics			

ACCESSORIES

Expandable Locking Well Cap: 2", 4", 6", or 8"

Hanger Bracket: Universal

Additional Suspension Cable: 3/32" per foot

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • FAX (303) 322-7242

email: sales@geotechenv.com • website: www.geotechenv.com