Water Quality Meters

YSI EcoSense EC300A Conductivity/Temperature Meter

The YSI EC300A is designed for guick, accurate results in an economical platform. The ability to measure conductivity, salinity, TDS and temperature in a simple compact instrument allows the instrument to be used across multiple application sampling strategies.

FEATURES

- IP67 Waterproof housing
- Rugged, weighted probe assembly
- Automatic temperature compensation
- 4- and 10-meter field cables available
- Conductivity, Salinity, TDS, Temperature
- Super-stable, four-electrode conductivity cell designed for the field
- Calibration back-up
- Audio feedback
- 1-Year instrument, electrode and cable warranty
- · Auto shutoff function after 30 minutes of inactivity
- 50 data set memory
- CE compliant
- Calibration solutions available

SPECIFICATIONS

Temperature:
D

Range Resolution Accuracy	-10° to +90°C (14° to 194°F) 0.1°C ±0.2°C or ±0.4%, whichever is greater
Conductivity:	0.0 μS to 200 mS, with auto ranging
<i>Range</i> 0 to 499.9 μS/cm 0 to 4999 μS/cm 0 to 49.99 mS/cm 0 to 200.0 mS/cm	$\begin{array}{ll} \textit{Resolution} & \textit{Accuracy (meter \& probe)} \\ 0.1 \ \mu\text{S/cm} & \pm(1\% \ \text{of reading } +2 \ \mu\text{S/cm}) \\ 1 \ \mu\text{S/cm} & \pm(1\% \ \text{of reading } +5 \ \mu\text{S/cm}) \\ 0.01 \ \text{mS/cm} & \pm(1\% \ \text{of reading } +0.05 \ \mu\text{S/cm}) \\ 0.1 \ \text{mS/cm} & \pm(1\% \ \text{of reading } +0.5 \ \text{mS/cm}) \end{array}$
Salinity: Range Resolution Accuracy	Calculated; 0.0 to 70.0 ppt 0.1 ppt ±0.2% FS
Total Dissolved Solids:	TDS in g/L calculated; enter constant values from 0.30 to 1.00, default value 0.65
General: Reference Temp Temp Coefficient Default Cell Constant Cell Constant Range	15.0° to 25.0°C (59° to 77°F) 0.0% to 4.0% 5.00 4.50 to 5.50

4.50 to 5.50 Thermistor, 10KΩ at 25°C



Operating Range:	
Temperature Relative Humidity	0° to 50°C (32° to 122°F) up to 95%
Size:	3.1" W x 7.25" L x 1.45" D (78mm x 184mm x 37mm)
Weight w/Battery:	0.6 lb. (272 gm)
Battery: Battery Life	One 9 volt included with purchase 500 hours
Calibration Back-up:	Yes
Audio Feedback:	Yes, all keys
Autolock Feature:	Yes
Memory:	50 data set reviewable memory
Auto Shutoff:	Automatically powers off after 30 minutes of inactivity
Water Rating:	IP67 Waterproof

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc. 2650 East 40th Avenue • Denver, Colorado 80205 (303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242 email: sales@geotechenv.com website: www.geotechenv.com

ATC Probe