Water Quality Meters

YSI EcoSense ODO200 Optical DO/Temperature

The ODO200 is designed for quick, accurate results in an economical platform. The ability to measure DO optically along with temperature, in a simple, compact handheld allows the instrument to be used across multiple application sampling strategies in the field. With a one-year instrument, probe and sensor cap warranty, IP67 water-proof case and ease-of-use, the EcoSense ODO200 will fit your needs.

FEATURES

- Automatic temperature compensation
- 1-year instrument, cable and sensor cap warranty
- 1-, 4- and 10-meter durable field cables available
- Manual input for salinity and pressure compensation
- · Low battery indicator with 100 hour battery life
- Replaceable optical sensor cap (12-18 month life)
- Auto shutoff function after 30 minutes of inactivity
- 50 data set reviewable memory
- IP67 waterproof rating



SPECIFICATIONS

Temperature	Range Resolution Accuracy	0 to 50°C (32 to 122°F) 0.1°C ±0.3°C
Dissolved Oxyger (% Air Saturation)	n Range Resolution Accuracy	0 to 200% 1 or 0.1% \pm 1.5% of reading or \pm 1.5%; whichever is greater
Dissolved Oxyger (mg/L)	n Range Resolution Accuracy	0 to 20 mg/L 0.01 mg/L ±1.5% of reading or ±0.15 mg/L; whichever is greater
Barometer (mBar)	Range Resolution	500 to 1125 mBar (manual input during calibration) 1 mBar
Salinity (ppt)	Range	0 to 40 ppt (manual input during calibration)
Operating Range	e Temperature Relative Humidity	0° to 50°C (32° to 122°F) up to 95%

Certifications		RoHS, WEEE, CE, IP67 waterproof
Size	Case	78 mm wide (widest point) x 184 mm long x 37 mm deep (3.1 in. x 7.25 in. x 1.45 in.)
	Sensor	19.05 cm long; 2.41 cm diameter (7.5 in. long; 0.95 in. diameter)
	Display	50.8 mm wide x 38.1 mm high (2 in. x 1.5 in.)
Weight with Battery		0.6 lb. (272 gm)
Battery		One 9 volt included with purchase; 100 hour battery life in manual mode; low battery indicator
Audio Feedback		Yes, all keys
Memory		50 data set reviewable memory
Auto Shutoff		Automatically powers off after 30 minutes of inactivity
Display		Segmented (shows D0 in mg/L or % along with temperature)

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc. 2650 East 40th Avenue • Denver, Colorado 80205 (303) 320-4764 • (800) 833-7958 • FAX (303) 322-7242 email: sales@geotechenv.com website: www.geotechenv.com